

Surface Preparation



Testex Tape

Complies with ASTM D-4417
Size: 3/8" diameter test area
Packaged 50 pieces to dispenser
Provides a permanent record.
Tape Grades

Testex Press-O-Film replica tape is available in a variety of thicknesses to facilitate profile measurement in differing ranges.

The primary range for measurement with replica tape is 0.8 to 4.5 mils (20 to 115 um). Use of Coarse Minus grade (<0.8 mil or <20 um) or X-Coarse grade tape (>4.5 mil or >115 um) should be restricted primarily to checking measurements at the lower and upper ends of the primary range.

Grades

Coarse Minus - 0.5 to 1.0 mils / 12 to 25 um

Coarse - 0.8 to 2.5 mils / 20 to 64 um

X-Coarse - 1.5 to 4.5 mils / 38 to 115 um

X-Coarse Plus - 4.6 to 5.0 mils / 116 to 127 um

Grades Available – Packet of 50

Coarse – Part Number T-20142-C

X-Coarse – Part Number T-20142-XC

X-Coarse Plus – Part Number T-20142-XCP

Please call our office for pricing

www.abss.net.au



Victoria:

18 Beckett Avenue
Keilor East, Vic 3033



1300 727 240



info@abss.net.au



NSW:

Unit 27
274-276 Hoxton Park Road
Prestons, NSW 2170



02 9607 9953

0411 653 972



info@abss.net.au